

NEW

OMRON

EtherCAT junction slaves

GX-JC03/JC06

For branching on EtherCAT networks


Effective wirings by combining daisy chaining and branching connections



EtherCAT®

Daisy chaining, star wiring, and tree connections can be made in one network. Efficiency in assembling and wirings will be improved, shortening the time required to start the system operation.

System configuration




Advantages of EtherCAT junction slaves

Support for efficient equipment and system building

In a system that consists of plural processes, debugging work can be started with a process for which designing work has been completed.


EtherCAT daisy chaining connection

The system can not start operation before installing and assembling all devices of all processes. (Neither Process B nor Process C can start operation before Process A has been built.)




EtherCAT daisy chaining connection

If an error occurs on a slave, or the network cable is disconnected, slaves following on the same network can not communicate with the master unit. The operating rate of the system can be lowered, or maintenance work will be less efficient.




EtherCAT branching connection

The slaves connected via EtherCAT junction slaves on Process B and Process C can operate, even though slaves for Process A do not operate. Debugging work of the processes can be made separately, thus improving debugging work efficiency.





EtherCAT branching connection

With EtherCAT junction slaves, each process can be designed and wired as separated blocks. If an error occurs on one slave device, operation of the process that uses the slave stops, but that will not influence the entire system operation. The EtherCAT junction slave will contribute to prevention of loss of workpieces in process and prompt system restoration.



Ordering Information

Product name	No. of ports	Dimensions	Power supply voltage	Model	Standards	
EtherCAT junction slaves		3	W25 x H90 x D78 mm	DC24V	GX-JC03	CE, UC1
		6	W48 x H90 x D78 mm	DC24V	GX-JC06	

EtherCAT(R) is a registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.

OMRON Corporation Industrial Automation Company
Tokyo, JAPAN

Contact: www.ia.omron.com

Regional Headquarters

OMRON EUROPE B.V.

Wegalaan 67-69-2132 JD Hoofddorp
The Netherlands
Tel: (31)2356-81-300/Fax: (31)2356-81-388

OMRON ELECTRONICS LLC

One Commerce Drive Schaumburg,
IL 60173-5302 U.S.A.
Tel: (1) 847-843-7900/Fax: (1) 847-843-7787

OMRON ASIA PACIFIC PTE. LTD.

No. 438A Alexandra Road # 05-05/08 (Lobby 2),
Alexandra Technopark,
Singapore 119967
Tel: (65) 6835-3011/Fax: (65) 6835-2711

OMRON (CHINA) CO., LTD.

Room 2211, Bank of China Tower,
200 Yin Cheng Zhong Road,
PuDong New Area, Shanghai, 200120, China
Tel: (86) 21-5037-2222/Fax: (86) 21-5037-2200

Authorized Distributor:

© OMRON Corporation 2011 All Rights Reserved.
In the interest of product improvement,
specifications are subject to change without notice.

Cat. No. R158

1011(1011)