

Packaging Machine Control Solutions

An electronic cam brings innovation to your packaging machines



Craftsmanship at your finger tips

Easily implement an electronic cam to middle-range packaging machinery

Our solution improves both packaging productivity and quality

Are you facing difficulties in introducing an electronic cam to your middle-range packaging machines due to cost reasons or technical reasons?



Omron offers solution “electronic cam control” to your packaging machines.

Issues on packaging machinery using conventional mechanical cam

Limit in performance

Difficult to reduce changeover time

Difficult to prevent packaging failure



Omron easily brings "craftsmanship" to packaging machinery to solve issues by;

High-speed control with electronic cam	_____	P. 4
Quick changeover driven by recipe	_____	P. 5
Prevent packaging failure by a variety of Function Blocks	—	P. 6
Easy design with Sysmac Library	_____	P. 7

Proposal using electronic cam system!

Improves productivity and quality in a cost effective way



High-speed control with electronic cam

Overcoming barrier to higher-speed and higher-precision packaging

The PLC and mechanical cam control cannot accurately synchronize axes.

In addition, low precision, vibration, and noise caused by mechanical cam limit high-speed and high-precision packaging.


Electronic cam optimizes packaging speed and precision

Electronic cam motion control realizes machine cam motion.

Electronic cam enables 3 axes - "film feeding", "product feeding", and "rotary knife" - to be synchronized at high speed.

This eliminates following errors between axes even during high-speed operation, leading to higher-speed and higher-quality packaging.

Packed with Omron's rich technical know-how on control programs, the Function Block (FB) makes advanced electronic cam control easy.



Function Block easily realizes electronic cam control

Omron's Rotary Knife Function Block brings higher speed and higher precision to horizontal flow packers and enables mechanical cam motion without electronic cam table.

Quick changeover driven by recipe

Overcoming barrier to improving productivity

- With conventional packaging machines using mechanical cam, operators have to rely on human experience during complex tuning, which increases changeover time and fails to improve packaging productivity.
- When restarting a packaging machine after stoppage, the machine occasionally produces empty packages due to home adjustment.

Easy and reliable changeovers without mechanical tuning


Digitalized data by electronic cams makes recipe-driven changeover possible.
On the HMI, simply register recipes and change them according to products for changeovers.
In this way, you can improve packaging productivity.




Recipe setting screen



Recipe selection screen



Contents of a recipe




Restart operation right after stoppage

Introducing an absolute encoder to the servo motor eliminates the need for homing operation when restarting operation after machine stoppage.
That means operation can be immediately resumed in the state when the product and film have been stopped.
Thanks to battery-free servo drive, battery replacement is no longer required.

1S AC Servo System
R88M-1□/R88D-1SN□-ECT



No need for homing



No battery required
for ABS encoder

Prevent packaging failure by a variety of Function Blocks

Overcoming barrier to improving packaging quality


- Empty packages and defectives caused by bite need to be removed at subsequent inspection.
- Defective packages may be produced until decrease in sealing temperature is detected after heater burnout.
- False detection of color marks printed on various packaging materials resulted in defective packaging.

Preventing packaging failure leads to good-looking packaging

By using the Rotary Knife FB and input signals from a sensor that detects position offset, the following “No product, No feed” and “No gap, No seal” functionalities can be easily added to prevent defective packaging and improve packaging quality.


• No product, No feed

When a product is not being fed, the film feeding stop till the next product is fed. This prevents empty packaging.




• No gap, No seal

Check the position offset when detecting the product. Predict the bit sealing from the set package length. The rotary knife and sealing stop.



Reduce defective packaging during heater burnout

Once a heater burnout is detected, the packaging operation stops, which prevents defective packaging that may produce during the decrease in heater temperature.



Stable detection of any packaging materials

The Color Mark Photoelectric Sensor stably detects color marks on both glossy and colorful materials, which prevents packaging failures caused by false detection.

Since any packaging materials can be read, the material can be cut at the exact timing, helping produce good-looking packages.



Easy design with Sysmac Library

Overcoming barrier to improving design efficiency

A lack of expertise makes it difficult to quickly design motion control from scratch.
In addition, testing programs is time-consuming.

Quick and reliable design


Omron provides the Sysmac Library that includes Function Blocks for horizontal flow packers to maximize the features of Omron products and simplify programming. You can easily design and modify horizontal flow packers.

Library usable for packaging machinery



- Rotary Knife Function Block
- Velocity Control Winder Function Block (Tension control)
- Box Motion Sample Program
- Temperature Control Library
- Direct Manipulated Variable Control Function Block (Direct power control)
- Quantitative Discharging Control Function Block (Weighing control)

In addition to sample programs using FBs in the Packaging Machine Library, HMI templates facilitate your design work.




One software for configuration and programming

The Sysmac Studio is used to set up servo systems, motion, and controllers.
Various servo setup functions make startup even easier and faster.




Data import from Motor Sizing Tool

Data import function for quick parameter setup.



Gain tuning to meet your way

Three types of functions for fast and accurate gain tuning.



Omron products for packaging control solutions

New HMI

NB Simple Programmable Terminal
NB7W-TW11B

HMI with 65,000 color display and
Ethernet connectivity ideal for
middle-range packaging machines.

New Controller

NX Machine Automation Controller
NX1P2-1140DT

Compact controller for motion control and data
handling is fully integrated within the Sysmac
automation platform.

Temperature Input Unit



EtherCAT

New Servo

1S AC Servo System
R88M-1□/R88D-1SN□-ECT

125 μs control cycle.
23 bit high resolution encoder.
Provides an accurate following control
in combination with the NX1P.



New Sensor

Color Mark
Photoelectric Sensor
E3S-DC

Offers stable detection of both
glossy and colorful packaging.





Software


Software components Sysmac Library
Packaging Machine Library
SYSMAC-XR012

The Sysmac Library is a collection of software functional components that can be used in programs for the NJ/NX-series Machine Automation Controllers or Industrial PC Platform NY-series IPC Machine Controller. "Packaging Machine Library" is packed with Omron's rich technical know-how to improve packaging quality and performance.



Automation Software
Sysmac Studio
SYSMAC-SE□□□

Fully compliant with open standard IEC 61131-3 and Japanese standard JIS B3503. One software for configuration of the NX Machine Automation Controller and 1S AC Servo System. Reusable programming code.



Omron offers solutions with the future in mind



Scalable from middle-range to high-end class

By using NJ5/ NX7, control program for middle-range packaging machines can be used to high-end machines with higher-speed and higher-precision. NA5 HMI screens support Pack ML.

Scalable control from middle-range to high-end packaging machines

NJ/NX Machine Automation Controller

Program for NX1P is usable to NJ501/NJ301/NJ101. Upgrading the controller enables higher-speed and higher-precision packaging and to design the expanded packaging line.

Minimum communications cycle



Sysmac machine control and IT technology

Industrial PC IPC Machine Controller

the IPC Machine Controller combines the precision and utility of the Sysmac platform with the versatility and range of Windows programs.



For reliable traceability and quality packaging



FQ2 Smart Camera
For printing inspection
(e.g. date, 2D code)



FH Vision System
For visual inspection
EtherCAT support vision sensor





Expand single packaging machine to whole packaging line

In combination with NJ5/NX7 and Sysmac solutions including transportation between machines, Pick and Place robots, vision system for inspection, you can build advanced packaging line.

For Pack ML and remote maintenance

Pack ML support screen



NA Programmable Terminal

NA introduces high level integration with NJ/NX (e.g. Tag sharing) and PC-based crystal clear view.



For European and US safety standards

NX Safety Controller


Adds safety system on the EtherCAT communications of packaging machine control. EtherCAT communications enables STO (Safe Torque Off) function without connecting to 1S Servo.



For transportation between packaging machines

Multi-function Compact Inverter 3G3MX2-V1

Provides a conveyor transportation between machines without adding controllers.



IO-Link

Detection of real time sensor status towards "eliminates packaging line stoppages"



GX IO-Link Master Unit
GX-ILM08C



NX IO-Link Master Unit
NX-ILM400



Proximity Sensor
(Standard model)
E2E-□-IL□



Proximity Sensor
(Spatter-resistant model)
E2EQ-□-IL□



Photoelectric Sensor
E3Z-□-IL□



Color Mark Photoelectric Sensor
E3S-DCP21-IL□

Meet a variety of changes in manufacturing



Industrial robot
Hornet/Quattro/Cobra/Viper

For high-quality and high-speed material handling for products positioning and boxing.

Product line up

Machine Automation Controller
NX1P

EtherNet/IP
EtherCAT



Model	Total number of built-in I/O points			Maximum number of used real axes		
		Number of input points	Number of output points		Used motion control servo axes	Used single-axis position control servo axes
NX1P2-1140DT	40 points	24 points	16 points NPN transistor	8 axes	4 axes	4 axes
NX1P2-1140DT1			16 points PNP transistor*			
NX1P2-1040DT			16 points NPN transistor	6 axes	2 axes	4 axes
NX1P2-1040DT1			16 points PNP transistor*			
NX1P2-9024DT	24 points	14 points	10 points NPN transistor	4 axes	0 axes	4 axes
NX1P2-9024DT1			10 points PNP transistor*			

* With the load short-circuit protection.

NX I/O

Digital I/O Units
NX-ID/IA/OD/OC/MD



Analog I/O Units
NX-AD/DA

HMI NB/NB Simple



Series	Model	Specifications	
NB/ NB Simple	NB3Q-TW01B	3.5 inch screen	Ethernet
	NB5Q-TW01B	5.6 inch screen	
	NB7W-TW01B	7 inch widescreen	
	NB7W-TW11B		
	NB10W-TW01B	10.1 inch widescreen	

1S AC Servo System
R88M-1□/R88D-1SN□-ECT



Temperature Input Unit/
Heater Burnout Detection Unit
NX-TS/HB



Load Cell Input Unit
NX-RS

Position Interface Unit
NX-ECO/ECS/PGO



Communication
Interface Units
NX-CIF

IO-Link
IO-Link Master Unit
NX-ILM400



System Units
NX-PD/RF/PC/TBX

Color Mark Sensor

Color Mark
Photoelectric Sensor
E3S-DC



Color Fiber Amplifier Unit
E3NX-CA



Automation Software
Sysmac Studio
SYSMAC-SE2□□□



Software components Sysmac Library
Packaging Machine Library
SYSMAC-XR012



PackML defines state and transition of packaging machine
Includes PackML Support Function Blocks

Related catalogs



Machine Automation Controller
NX1P
Cat.No. P115



Programmable Terminal
NB Simple
Cat.No. V438




AC Servo System
1S series
Cat.No. I821



Sysmac Library
Packaging Machine Library
SYSMAC-XR012
Cat.No. P111




Color Mark Photoelectric Sensor
E3NX-CA/E3S-DC
Cat.No. Y216



NJ/NX Controller
Cat.No. P089



Sysmac Automation Platform
Cat.No. P079



Sysmac Catalog
Cat.No. P072

Sysmac is a trademark or registered trademark of OMRON Corporation in Japan and other countries for OMRON factory automation products.

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.

EtherNet/IP™ is the trademarks of ODVA.

Other company names and product names in this document are the trademarks or registered trademarks of their respective companies.

The product photographs and figures that are used in this catalog may vary somewhat from the actual products.

Microsoft product screen shot(s) reprinted with permission from Microsoft Corporation.

Terms and Conditions Agreement

Read and understand this catalog.

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

Warranties.

- (a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.
- (b) Limitations. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE.

Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty.

See <http://www.omron.com/global/> or contact your Omron representative for published information.

Limitation on Liability; Etc.

OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY.

Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.

Suitability of Use.

Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT(S) IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

Programmable Products.

Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.

Performance Data.

Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.

Change in Specifications.

Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.

Errors and Omissions.

Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.

OMRON Corporation Industrial Automation Company
Tokyo, JAPAN

Contact: www.ia.omron.com

Regional Headquarters

OMRON EUROPE B.V.

Wegalaan 67-69-2132 JD Hoofddorp
The Netherlands

Tel: (31)2356-81-300/Fax: (31)2356-81-388

OMRON ELECTRONICS LLC

2895 Greenspoint Parkway, Suite 200
Hoffman Estates, IL60169 USA

Tel: (1) 847-843-7900/Fax: (1) 847-843-7787

OMRON ASIA PACIFIC PTE. LTD.

No. 438A Alexandra Road # 05-05/08 (Lobby 2),
Alexandra Technopark,
Singapore 119967

Tel: (65) 6835-3011/Fax: (65) 6835-2711

OMRON (CHINA) CO., LTD.

Room 2211, Bank of China Tower,
200 Yin Cheng Zhong Road,
PuDong New Area, Shanghai, 200120, China
Tel: (86) 21-5037-2222/Fax: (86) 21-5037-2200

Authorized Distributor:

© OMRON Corporation 2016 All Rights Reserved.
In the interest of product improvement,
specifications are subject to change without notice.

CSM_2_1_1216

Cat. No. Y219-E1-02

1216 (0916)